

#### **Internal Hard Drives**

**S300** 

### Capture every detail



10 8 6 5 4 TB TB TB TB TB

Color



Toshiba's 3.5-inch S300 Surveillance Hard Drive is designed and tested for 24/7 reliable surveillance, built for speed, capacity, and longer content retention. Capture and analyse every frame from up to 64 video cameras in high resolution with the S300. Space is important to continually capture a history of video evidence over a period of time. With up to 10 TB you get the capacity to record and play back the events in real-time in high resolution and with object identification and face recognition.

#### Use for:

- Surveillance Digital Video Recorders (sDVR)
- Surveillance Network Video Recorders (sNVR)
- Hybrid sDVR (analog and IP)
- RAID Storage Arrays for Surveillance



3.5" SATA Hard Drive

**RPM** 7200 rpm

256 / 128 MB buffer

24/7 operation

Supports up to 64 video cameras

High reliability and enhanced real-time performance

Toshiba Dynamic Cache Technology
Toshiba Stable Platter Technology

High-endurance design

3-year warranty

#### **Manual**

Toshiba\_Installation\_and\_Safety.pdf 🕹


Tools

TOSHIBA\_Storage\_Diagnostic\_Tool.zip 🕹





# **Product Specifications**



### **Basic Specifications**

Form factor	3.5-inch
Interface	6.0 Gbit/s
Number of cameras supported	64 (6 TB -10 TB), 32 (4 TB, 5 TB)
Max. transfer rate	248 MB/s Typ. (10 TB), 241 MB/s Typ. (6 TB, 8 TB), 157 MB/s Typ. (4 TB, 5 TB)
Drive bays supported	8+ (6 TB -10 TB), 1-8 (4 TB, 5 TB)
Rotational Vibration (RV) Sensors	Yes
Advanced Format (AF)	Yes
RoHS compatible	Yes
Halogen Free	Yes
Shock Sensor	Yes

#### Performance

Rotational speed	7200 rpm
Buffer size	256 MB (6 TB - 10 TB), 128 MB ( 4 TB, 5 TB)
Average latency	4,17 ms (6 TB - 10 TB), 5,56 ms (4 TB, 5 TB)
Native Command Queing (NCQ)	Supported

### Reliability

Workloads	180 TB/year (6 TB - 10 TB), 110 TB/year (4 TB, 5 TB)
MTTE	1.000.000 hours

Unrecoverable error rate	1 per 10E14 bits read
24/7 operation	Yes
Load / Unload Cycle	600.000
Limited warranty	3 years

#### **Power Management**

Supply voltage	5V DC +6/-5%; 12V DC ±10% (6TB - 10TB); 5V DC ±5%; 12V DC ±10% (4TB, 5TB)
Consumption - Read/Write	9.48 W typ. (10 TB), 8.61 W typ. (8 TB), 7.88 W typ. (6 TB), 7.5 W typ. (4 TB, 5 TB)
Consumption - Low Power Idle	7.15 W typ. (10 TB), 6.33 W typ. (8 TB), 5.59 W typ. (6 TB), 4.00 W typ. (4 TB, 5 TB)

#### **Environmental**

Temperature (operating / non-operating)	0 - 70° C / -40 - 70° C
Vibration (operating)	0.75 G (5 to 300 Hz) 0.25 G (300 to 500 Hz)
Vibration (non-operating)	3.0 G (5 to 500Hz) (6 TB - 10 TB); 5 G (5 to 500Hz) or less (4 TB, 5 TB)
Shock (operating)	70 G / 2 ms duration
Shock (non-operating)	250 G / 2 ms duration (6 TB - 10 TB), 300 G / 2 ms duration (4 TB, 5 TB)
Acoustics (idle mode)	34 dB typ. (6 TB - 10 TB), 26 dB typ. (4 TB, 5 TB)

### Physical

Dimensions	147 (L) x 101.85 (W) x 26.1 (H) mm
Weight (approx.)	770 g max. (6 TB - 10 TB), 720 g max. (4 TB, 5 TB)

#### **Box Content**

Box Content	3.5-inch internal HDD - S300
	Surveillance Hard Drive

### Product Range

Part number	Capacity	Color
HDWT31AUZSVA (Bulk)	10 TB	-
HDWT380UZSVA (Bulk)	8 TB	-
HDWT360UZSVA (Bulk)	6 TB	-
HDWT150UZSVA (Bulk)	5 TB	-
HDWT140UZSVA (Bulk)	4 TB	-

## Logistical Information:

n/A Box dimensions Box weight (gross) n/A

Master carton dimensions 321 x 406 x 213 mm

Master carton weight (gross) 16 kg (typ.), 11 kg (ty

Boxes per master carton 20 16 kg (typ.), 11 kg (typ.) (1TB, 500GB)

Pallet dimensions n/A Pallet weight (net) n/A Units per pallet 180

### Contact

**Toshiba Electronics Europe GmbH** 

Hansaallee 181 40549 Düsseldorf Germany